

Datasheet

EN6200

PRIME OCTA 930D-4X

Next Generation Firewall



Extended
Ports
With
Three Layer
Security,
SDWAN
And
Ascendable
Users

EN6200-Prime is designed keeping in mind the requirement of pay as you grow model which is most required for the current market conditions.

Compared to the other product's Tacitine moved one step ahead of providing a comprehensive solutions to meet customer IT needs on seamless failover between the private cloud and alternate Internet connection, secure branch connectivity with 100% uptime and remote manageability coupled with 2x scalability.

EN6200 Prime's scalability feature ensures 60% saving on capex cost on new NGFW purchase when the organization grows 2x on their user numbers.

Tacitine NGFW's inbuilt logs and elaborated reports on every configured features make EN6200 Prime not just a NGFW, instead it is informative, proactive on security breaches, easy to use and provides complete control of the network.

In addition to NGFW features, Prime Series are equipped with AAA Hotspot features for individual user control on both wired and wireless network.

Prime Series supports 3G/4G dongles and hotspot along with multiple wired internet connections for auto failover and load balancing.

EN6200 Prime Series are versatile, scalable, robust and rack mountable.

Specifications

Performance Parameters	EN6200 PRIME OCTA 930D-4X
Concurrent Sessions	56M
New Sessions/sec	450K
Firewall Throughput - Test Condition (Gbps)	50 / 70
Firewall Throughput - Real World (Gbps)	40 / 63
IPSec VPN Throughput (Gbps)	10
Firewall Latency (64 byte, UDP)	4.8µs
No. of WAN Ports	8
IPSec (Site-Site) & IPSec VPN Peers	10000 & 10000
Site to Site / Client to SSL VPN	100 / 5000
NGIPS Signature supported	35000
Dynamic Routing	RIP V1/V2, OSPF & BGP
IPv6 Ready	Yes
Encryption Supported	3DES, AES-CBC (128/256/512), AES-GCM (128/256/512) CAMELLA-CBC (128/256), BlowFish-128-CBC
Authentication Algorithm	MD5, SHA-1, SHA256, SHA384, SHA 512
Firewall Policies	Unlimited
High Availability License & Dedicated Port	Yes / 2x1G HA Port
Licensed LAN Users	Unlimited
Hardware Specification	
Gigabit Ethernet Ports	1xLAN + 15xLAN/WAN + 8x1G SFP + 4x10G SFP+
Type of Processor / RAM DDR3	X86 / 16GB
Storage (SSD)	500 GB
USB / VGA Port	2/1
Form Factor	1U Rackmount
Dimensions (mm) - (HxWxD)	44x230x265
Weight (Kg) / Color	10 / Black
Power Supply	Dual
Redundant Fan	Yes
Expansion Slot	4 / Options are 4x10G SFP+ / 8x1G SFP / 8x1GE
Consumption	60W
Total Heat Dissipation (BTU)	160
Operating Temperature	0-45° C
Storage Temperature	2-70° C
Relative Humidity (NC)	10 to 90%
Regulatory Compliance	FCC Part 15, Class B, CE

All specification and photos are subject to change without prior notice.

1. Maximum throughput performance is measured under ideal test conditions using industry standard performance test tools. 2. Firewall UDP throughput performance is based on RFC 2544 guidelines. 3. All Performance values are upto or rough guideline only and vary depending on system configuration. 3. IPS throughput(http) measured using default IPS rule set and 512KB object size. 4.VPN throughput measured using multiple tunnels with 512KB response size. 5. Testing done with multiple flows through multiple port pairs. * lperformance numbers vary based on the ports and the modules populated. * Appliance picture is for understanding purpose, actual look and feel changes based on the add on cards getting populated

Ordering Information

EN6200-Prime Octa-930D-4X-Y	18x1GE, 8x1G SFP & 4x10G SFP+ device includes AV/CF/AS/IDS/IPS/AAA/HW Warranty subscription with "D" for Dual PSU and "Y" Support.
Y = Subscription years options : 1 Year or 3 Years or 5 Years	
4x - 4 Expansion Slot Options : 4x10G SFP+ 8x1G SFP 8x1GE	

Tacitine Assured Support

Tacitine products come with direct OEM 24/7 support by trained Professionals for product configuration and support. TAS helps customer on security best practices to make the network hacker free and more reliable.



www.tacitine.com

Features

- Router (Static & Dynamic)
- Bandwidth Aggregation
- Scalable Users ₃₂
- Auto Load Balancer & Failover
- Quality based link Failover
- 4095 VLAN with L3 Support
- SPI Firewall & Geo Fencing
- Web Security
- Application & Content Filter
- Email Security
- GAV, IDS/IPS & WAF
- TFA & MFA Support
- 200 + Protocols support
- AAA User Management
- VPN - SSL / IPSec / Crypto
- QoS & SDWAN
- DDNS/SNMP/Remote sys log
- Traffic Analyzer
- Inbuilt Logs & Reports

Tacitine Consulting Pvt Ltd,

6/1, 1st Main,

Behind Kodava Samaj, Vasanth Nagar,
Bangalore – 560 052.

India | USA | Middle East | South East Asia